

CLAMSHELL CARDS

Dimension: 86 x 54 x 0.8 mm

Standard Color White

IC Available: EM4100, EM4102, EM4550, NXP Hitag1, Hitag2, HitagS256, HitagS2048



ISO CARDS

Dimension: 86 x 54 x 0.8 mm

Material: PVC or Pet

Offset, Screen Personalisation, Serial Number Printing

IC Available 125 Khz: EM4100, EM4102, EM4550, NXP

IC Available 13.56 MHZ: NXP Mifare S50, NXP Mifare S70, Mifare DESFire 4KB/8KB, ICODE1, ICODE2 SLI, PicoPass, HiTag1, Hitag2, HitagS256, HitagS2048

IC Available 865-867 MHZ: UCode Gen2, Impinj, Monza, Alien



COMBI / DUAL FREQUENCY CARDS

Dimension: 86 x 54 x 0.8 mm

Material: PVC or PET

Offset, Screen, Personalisation, Serial Number Printing



RFID ABS KEYFOBS

AB0001 43.7x30x5x5.3	AB0002 35.3x28x6.4	AB0003 40.5x32x4.2	AB0004 46x28x5	AB0005 53x37.5x9.8	AB0006 52.5x35.2x9	AB0010 34.8x23x3.9	AB0016 53.9x33.8x5	AB0017 37x30x5
ABD17 17dia x 3.5	ABD22 22dia x 2.4	ABD30-1 30dia x 3	ABD30-3 30dia x2 x 3mm Hole	ABD30S1 30dia x2 x 5mm Hole	ABD50-1 50dia x2 x 5mm Hole	ABD50-2 50dia x5 x 5mm Hole	ABD30-4 30dia x 4	ABD35 35dia x 4 3.8mm Hole

IC Available 125 KHz: EM4100, EM4102, EM4550, NXP HiTag1, HiTag2, HiTagS256, HiTagS2048

IC Available 13.56 MHz: NXP Mifare S50, NXP Mifare S70, Mifare DESFire 4 KB / 8 KB, ICODE1, ICODE2 SLI, PicoPass

RFID LAUNDRY TAGS

Physical Parameter																
Diameter ±0.5mm	9	10	11	12	13	14	15	16	17	18	20	22	24	26	28	30
Thickness ±0.3mm	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5
Weight ± 5%	.25	.35	.40	.45	.55	.60	.70	.85	.90	.95	1.20	1.50	1.70	2.00	2.40	2.50

IC Available 125 KHz: EM4100, EM4102, EM4550, NXP HiTag1, HiTag2, HiTagS256, HiTagS2048

IC Available 13.56 MHz: NXP Mifare S50, NXP Mifare S70, Mifare DESFire 4 KB / 8 KB, ICODE1, ICODE2 SLI, PicoPass

IC Available 865-867 MHz: Ucode Gen2, Impinj, Monza, Alien

RFID WRISTBAND AND SPECIAL TAGS

Silicon Wristband	Screw Tags	Ferrite Core Inlay	Metal Tag	Glass Tag

IC Available 125 KHz: EM4100, EM4102, EM4550, NXP HiTag1, HiTag2, HiTagS256, HiTagS2048

IC Available 13.56 MHz: NXP Mifare S50, NXP Mifare S70, Mifare DESFire 4 KB / 8 KB, ICODE1, ICODE2 SLI, PicoPass

IC Available 865-867 MHz: Ucode Gen2, Impinj, Monza, Alien

PREPRINTED SMART CARDS



CALL - 9731118504

SMART CARDS